

01-049-0360-0

Januar 2007

May 2007

DE20070524

Anleitung: Ölablassschraube  
BMW G 650 X Challenge

Instruction: Oil Drain Plug  
BMW G 650 XChallenge



Lieferumfang:

**1 x Ölablassschraube**

**1 x Dichtring Kupfer**

Contents:

**1 x Oil drain plug**

**1 x Seal ring copper**

**Achtung! Wichtige Hinweise**

**Ablausschraube mit 35Nm anziehen**

**Attention! Important notes:**

**Tighten to max. 35Nm torque!**

**Montage:**

1. Bei Ölwechsel die Original-Ablausschraube gegen die neue tauschen und mit neuem Dichtring montieren. Mit 35 Nm anziehen.

2. Ohne Ölwechsel .Das Motorrad auf die linke Seite waagrecht hinlegen , die Original-Ablausschraube gegen die neue tauschen und mit neuem Dichtring Montieren. Mit 35 Nm anziehen.

**Assembly:**

1. Replace the original oil drain plug with the new Touratech drain plug during oil change. Use new copper seal ring and tighten to max. 35Nm torque.

2. Exchanging drain plug without draining the oil: Set motorcycle on the ground horizontally so that the oil won't run out. Remove original plug and replace with Touratech drain plug. Tighten to max. 35Nm torque.